

# TAC エコダクト

## 標準寸法・物性

呼び径		内径 mm	外径 mm	ピッチ mm	参考質量 g/m	定尺 m	許容圧力 (常温)		許容減圧力 (常温)		許容曲げ 半径 mm
mm	inch						Mpa	kgf/cm <sup>2</sup>	kPa	mmHg	
32	1 1/4	32.0	38.0	7.5	170	30	0.04	0.4	-50.7	-380	40
38	1 1/2	38.0	45.0	7.8	235	30	0.04	0.4	-50.7	-380	50
50	2	50.8	59.0	10.0	325	30	0.04	0.4	-50.7	-380	60
65	2 1/2	63.5	72.0	12.5	405	30	0.03	0.3	-50.7	-380	75
75	3	76.2	85.0	13.0	470	30	0.03	0.3	-33.0	-248	90
90	3 1/2	88.9	99.0	13.5	575	30	0.03	0.3	-20	-150	90
100	4	101.6	111.5	15.0	635	30	0.03	0.3	-17.5	-131	110
125	5	127.0	138.5	21.0	975	20	0.02	0.2	-12.5	-94	135
150	6	152.4	164.0	20.0	1125	20	0.02	0.2	-12.5	-94	160
200	8	203.2	216.0	22.5	1545	20	0.01	0.1	-6.0	-45	210
250	10	252.0	271.0	26.0	2975	10	0.01	0.1	-4.0	-30	300
300	12	303.0	322.0	26.0	3735	10	0.01	0.1	-2.5	-19	350

※脱塩ビダクトカフスも用意しております(Φ 250、Φ 300を除く)。