

TAC ダクトEE

標準寸法・物性

呼び径		内径 mm	外径 mm	ピッチ mm	参考質量 g/m	定尺 m	許容圧力 (常温)		許容減圧力 (常温)		許容曲げ半径 mm
mm	inch						Mpa	kgf/cm ²	kPa	mmHg	
32	1 1/4	32.4	38.6	8.4	220	50	0.06	0.6	-66.0	-495	32
38	1 1/2	37.3	44.5	9.2	295	50	0.06	0.6	-66.0	-495	38
50	2	50.6	60.2	10.0	585	30	0.05	0.5	-66.0	-495	50
65	2 1/2	62.4	72.0	12.0	645	30	0.04	0.4	-66.0	-495	65
※75	3	76.4	86.4	13.0	775	30	0.04	0.4	-33.0	-248	75
※90	3 1/2	88.9	99.5	13.5	945	30	0.03	0.3	-33.0	-248	90
※100	4	101.6	112.2	15.0	1020	30	0.03	0.3	-21.5	-161	100
※115	4 1/2	114.3	125.9	17.4	1255	20	0.03	0.3	-20.0	-150	110
125	5	125.9	138.7	21.0	1350	20	0.02	0.2	-20.0	-150	125
150	6	152.4	164.8	20.0	1670	20	0.02	0.2	-14.5	-109	150
※165	6 1/2	165.0	177.8	22.0	1770	20	0.02	0.2	-10.0	-75	150
175	7	177.8	190.6	20.0	1935	20	0.02	0.2	-10.0	-75	175
200	8	203.7	217.1	22.5	2190	20	0.01	0.1	-6.0	-45	200
225	9	227.0	240.4	23.5	2440	10	0.01	0.1	-5.5	-41	225
250	10	252.0	266.2	25.0	2950	10	0.01	0.1	-4.5	-34	250
275	11	278.0	292.6	28.0	3150	10	0.01	0.1	-4.0	-30	275
300	12	303.0	318.0	30.0	3480	10	0.01	0.1	-3.0	-23	300

※印のサイズは鋼管に直結できます。