

カナアルミダクト

規格

型番(注)	呼称		内径 mm	外径 mm	ピッチ mm	参考質量 g/m	定尺 m	許容圧力(常温)	許容減圧力(常温)	許容 曲げ半径 mm以上	使用温度 範囲 (°C)
	mm	インチ						Mpa以下 [kgf/cm ²]	Mpa以上 [kgf/cm ²]		
DC-AL-038-05	38	1 1/2	42.7	45.0	10.8	128	5	0.020[0.20]	-0.033[-0.34]	30	10~80
DC-AL-050-05	50	2	53.0	55.3	10.8	175	5	0.020[0.20]	-0.033[-0.34]	35	10~80
DC-AL-065-05	65	2 1/2	68.0	70.3	10.8	222	5	0.020[0.20]	-0.033[-0.34]	45	10~80
DC-AL-075-05	75	3	78.0	80.3	10.8	259	5	0.010[0.10]	-0.027[-0.28]	55	10~80
DC-AL-100-05	100	4	103.0	105.3	10.8	338	5	0.010[0.10]	-0.017[-0.17]	70	10~80
DC-AL-117-05	117	4 1/2	117.0	119.3	10.8	385	5	0.010[0.10]	-0.013[-0.14]	75	10~80
DC-AL-125-05	125	5	128.0	130.3	10.8	422	5	0.010[0.10]	-0.010[-0.10]	90	10~80
DC-AL-150-05	150	6	153.0	155.7	10.8	644	5	0.010[0.10]	-0.010[-0.10]	105	10~80
DC-AL-175-05	175	7	178.0	180.7	10.8	749	5	0.010[0.10]	-0.010[-0.10]	120	10~80
DC-AL-200-05	200	8	203.0	205.7	10.8	855	5	0.010[0.10]	-0.007[-0.07]	150	10~80
DC-AL-225-05	225	9	228.0	230.7	10.8	960	5	0.009[0.09]	-0.007[-0.07]	170	10~80
DC-AL-250-05	250	10	253.0	255.9	10.8	1220	5	0.008[0.08]	-0.007[-0.07]	185	10~80
DC-AL-275-05	275	11	278.0	280.9	10.8	1338	5	0.008[0.08]	-0.007[-0.07]	185	10~80
DC-AL-300-05	300	12	303.3	305.9	10.8	1462	5	0.007[0.07]	-0.004[-0.04]	230	10~80