

クリスタルホース F-3型

●寸法および特性(品番 F3-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20℃) Mpa以下/ [kgf/cm ² 以下]	減圧変形温度 (-0.1Mpa/ -760mmHg) (℃)	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
19	19.0±0.5	24.5	6.0	0.60 [6.1]	70	115	220	20・50
25	25.4±0.5	30.4	6.0	0.50 [5.1]	65	275	270	
32	32.0±0.5	38.0	6.5	0.45 [4.6]	65	375	400	
38	38.1±0.5	44.0	7.0	0.40 [4.1]	60	475	545	
50	50.8±1.0	58.0	8.0	0.30 [3.1]	60	610	810	
65	63.5±1.0	72.2	8.5	0.30 [3.1]	55	800	1,200	
75	76.2±1.0	85.1	9.0	0.25 [2.5]	55	1,360	1,440	
90	89.0±1.0	99.5	9.5	0.25 [2.5]	55	1,400	1,945	
100	101.6±1.5	113.2	10.0	0.25 [2.5]	55	1,450	2,500	
125	127.0±1.5	139.5	11.0	0.25 [2.5]	50	2,500	3,100	20
150	152.4±1.5	167.5	13.0	0.25 [2.5]	50	2,900	4,180	10・20
200	203.0±1.5	221.5	17.2	0.20 [2.0]	45	3,000	7,170	