

タイパワーホース WR型

●寸法および特性(品番 WR-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20℃) Mpa以下/ [kgf/cm ² 以下]	減圧変形温度 (-0.1Mpa/ -760mmHg) (℃)	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
38	38.1±0.5	52.3	9.0	1.00 [10.2]	65	400	960	50
50	50.8±1.0	66.8	10.0	1.00 [10.2]	65	450	1,300	20・50
65	63.5±1.0	81.8	14.3	1.00 [10.2]	65	550	1,700	
75	76.2±1.0	97.0	15.1	1.00 [10.2]	65	750	2,200	
100	101.6±1.5	128.0	16.5	1.00 [10.2]	65	1,250	4,200	20・(50)
125	127.0±2.0	156.1	22.0	1.00 [10.2]	60	1,500	5,320	
150	152.4±2.0	187.0	24.0	1.00 [10.2]	60	2,000	7,260	
200	203.0±2.0	245.0	25.0	1.00 [10.2]	60	2,250	12,800	10・20
250	254.0±2.5	300.0	27.0	1.00 [10.2]	50	4,000	18,230	5
300	304.8±2.5	351.0	28.0	0.50 [5.1]	50	5,000	21,320	