

タイフレキホース P型・P-2型

●寸法および特性(品番 P-□・P2-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20°C) Mpa以下/ [kgf/cm ² 以下]	許容減圧力 (20°C) KPa以下/ [mmHg以下]	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
38	37.5	41.5±0.8	9.5	0.018 [0.18]	-17.0 [-130]	30	140	5
50	53.5	57.5±1.0	11.0	0.014 [0.14]	-17.0 [-130]	40	180	
65	67.0	71.0±1.0	11.5	0.011 [0.09]	-17.0 [-130]	50	240	
75	76.5	80.5±1.0	12.0	0.009 [0.09]	-17.0 [-130]	60	270	
90	92.0	96.0±1.0	14.0	0.007 [0.07]	-17.0 [-130]	70	320	
100	102.0	106.0±1.0	14.0	0.007 [0.07]	-17.0 [-130]	75	365	
125	127.5	131.5±1.0	15.0	0.005 [0.05]	-11.0 [-85]	90	435	
150	155.0	159.0±1.0	15.0	0.004 [0.04]	-8.0 [-62]	110	530	
200	202.0	208.0±1.0	19.3	0.003 [0.03]	-6.0 [-45]	140	1,020	
250	253.5	259.5±1.0	19.3	0.002 [0.02]	-5.0 [-35]	180	1,270	
300	302.0	308.0±1.5	24.0	0.002 [0.02]	-4.0 [-30]	230	1,350	

(注)内径は線下内径です。