

# タイフレキホース V型SUSタイプ

## ●寸法および特性(品番 SUS-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20°C) Mpa以下/ [kgf/cm <sup>2</sup> 以下]	許容減圧力 (20°C) KPa以下/ [mmHg以下]	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
50	50.8±1.0	53.8	20.0	0.018 [0.18]	-21.0 [-160]	60	330	2
65	65.5±1.0	69.0	20.0	0.015 [0.15]	-21.0 [-160]	70	430	
75	75.5±1.0	79.0	20.0	0.013 [0.13]	-21.0 [-160]	80	480	
90	91.0±1.0	94.5	24.0	0.010 [0.10]	-17.0 [-129]	95	550	
100	101.5±1.5	105.0	24.0	0.010 [0.10]	-15.0 [-115]	105	560	
125	126.0±1.5	129.5	24.0	0.010 [0.10]	-15.0 [-115]	125	740	
150	152.0±1.5	155.5	24.0	0.008 [0.08]	-13.0 [-100]	150	830	
(175)	177.0±2.0	180.5	24.0	0.006 [0.06]	-10.0 [-78]	175	1,060	
200	202.0±2.0	205.5	24.0	0.005 [0.05]	-9.0 [-70]	200	1,080	
250	253.5±2.5	257.0	24.0	0.003 [0.03]	-6.0 [-45]	255	1,400	
(275)	278.0±2.5	281.5	24.0	0.003 [0.03]	-6.0 [-45]	280	1,550	
300	304.0±3.0	307.5	24.0	0.002 [0.02]	-6.0 [-45]	305	1,650	

( )は受注生産品です。