

ダクトホースD型

規格

型番(注)	長さ(M)	呼称		内径 mm	外径 mm	ピッチ mm	参考質量 g/m	定尺 m	許容圧力(常温) Mpa以下 [kgf/cm ²]	許容減圧力(常温) Mpa以上 [kgf/cm ²]	許容 曲げ半径 mm以上
		mm	インチ								
DC-D-032-	T	32	1 1/4	32.4	38.6	7.5	250	50	0.06[0.6]	-0.067[-0.68]	32
DC-D-038-	T	38	1 1/2	37.3	44.5	7.9	350	50	0.06[0.6]	-0.067[-0.68]	38
DC-D-050-	T	50	2	50.8	59.8	11.0	550	50	0.05[0.5]	-0.067[-0.68]	50
DC-D-065-	T	65	2 1/2	64.0	73.2	11.1	700	30	0.04[0.4]	-0.067[-0.68]	65
DC-D-075-	T	75	3	76.5	85.9	11.7	800	30	0.04[0.4]	-0.033[-0.34]	75
DC-D-090-	T	90	3 1/2	90.0	100.0	12.0	950	30	0.03[0.3]	-0.033[-0.34]	90
DC-D-100-	T	100	4	103.0	113.0	12.0	1200	30	0.03[0.3]	-0.023[-0.23]	100
DC-D-125-	T	125	5	127.3	137.3	12.1	1450	20	0.02[0.2]	-0.012[-0.12]	125
DC-D-150-	T	150	6	151.4	162.0	13.5	1800	20	0.02[0.2]	-0.010[-0.10]	150
DC-D-175-	T	175	7	176.6	187.8	13.7	2000	20	0.01[0.1]	-0.008[-0.08]	175
DC-D-200-	T	200	8	205.0	216.8	14.3	2600	20	0.01[0.1]	-0.007[-0.07]	200
DC-D-250-	T	250	10	252.1	263.9	13.9	3300	10	0.01[0.1]	-0.004[-0.04]	250
DC-D-275-	T	275	11	278.0	290.6	15.3	3800	10	0.01[0.1]	-0.004[-0.04]	275
DC-D-300-	T	300	12	303.0	315.6	15.7	4000	10	0.01[0.1]	-0.003[-0.03]	300

* カフスのφ 175はゴム製(EPDM)です。 * 取付けカフスは全てオプションです。

(注) 末尾のTは定尺を指します。カットの場合はM単位で長さが入ります。(例)「φ 100を15Mの場合」DC-D-100-15